

Conventional Domed (CDD)

Burst Pressure Range in barg(psig) at 20C (68F)									
Standard Materials									
Nominal Bore		Stainless Steel		Aluminium		Nickel/Monel		Inconel	
mm	inch	min	max	min	max	min	max	min	max
15	0.5	40(580)	1400(20305)	4(58)	60(870)	20(290)	1000(14504)	70(870)	1400 (20305)
25	1	20 (290)	650(9428)	2(29)	30(435)	10(145)	500(7252)	35(508)	650 (9428)
40	1.5	20(290)	600(8702)	1.6(23)	20(290)	8(116)	400(5801)	25(363)	600 (8702)
50	2	17(247)	200(2900)	1.5(22)	15(218)	6(87)	200(2900)	20(290)	200 (2900)
65	2.5	16(232)	200(2900)	1.5(22)	14(203)	6(87)	200(2900)	18(261)	200 (2900)
80	3	15(218)	200(2900)	1.5(22)	12(174)	5(73)	200(2900)	15(218)	200 (2900)
100	4	15(218)	200(2900)	1.2(17)	10(145)	5(73)	150(2176)	15(218)	200 (2900)
150	6	12(174)	160(2320)	1(14.5)	8(116)	4(58)	100(1450)	15(218)	160 (2320)
200	8	10(145)	120(1740)	0.8(11.6)	7(102)	4(58)	80(1160)	12(174)	120 (1740)
250	10	8(116)	100(1450)	0.7(10.2)	6(87)	4(58)	70(1015)	10(145)	100 (1450)
300	12	6.5(94)	80(1160)	0.6(8.7)	5(73)	4(58)	60(870)	8(116)	80 (1160)
350	14	6.5(94)	70(1015)	0.5(7.3)	4(58)	4(58)	50(725)	8(116)	70 (1015)
400	16	6.5(94)	60(870)	0.5(7.3)	3(44)	4(58)	50(725)	7(101)	60 (870)
450	18	6(87)	55(797)	0.5(7.3)	2(29)	4(58)	45(653)	7(102)	55 (797)
500	20	5.5(80)	50(725)	0.5(7.3)	2(29)	4(58)	40(580)	6(87)	50 (725)
600	24	5(73)	40(580)	1(14.5)	2(29)	3(44)	30(435)	5(73)	40 (580)
700	28	4(58)	35(509)	1(14.5)	1.5(22)	2.5(36)	24(348)	4(58)	35 (509)
800	32	3(44)	30(435)	1(14.5)	1.2(17)	2(29)	20(290)	3(44)	30 (435)

Performance Tolerance (Zero Manufacturing Design Range)			
Burst Pressure	Tolerance	Burst Pressure	Tolerance
≤2 barg	+/- 0.1 barg	≤29 psig	+/- 1.45 psig
>2 barg	+/- 5%	>29 psig	+/-5%

Note: with an aluminium disc the above performance tolerances are increased by 5%

Free Flow Area / Minimum Net Flow Area (MNFA)					
Nominal Bore		No Vac Support (XXX)		Non-Opening Vac Support (NVS)	
mm	inch	mm ²	inch ²	mm ²	inch ²
25	1	507	0.78	383	0.59
40	1.5	1257	1.95	905	1.41
50	2	2027	3.14	1493	2.33
65	2.5	3318	4.78	2155	3.36
80	3	5027	7.39	3598	5.61
100	4	8107	12.57	5110	7.97
150	6	17671	27.39	11187	17.44
200	8	31416	48.7	19220	29.98
250	10	49087	76.09	31915	49.78
300	12	70686	109.6	-	-
350	14	96211	135.2	-	-
400	16	125664	176.7	-	-
450	18	159043	223.6	-	-
500	20	196350	278	-	-
600	24	282743	440.98	-	-
700	28	-	-	-	-
800	32	-	-	-	-